

DIGITAL CAP SENS STAINLESS STEEL A/V ENTRANCE PANEL - SBC

Flush-mounted entrance panel with 3mm thick stainless steel plate. Complete with 128x64 dot LCD graphic display and 15 buttons integrated into the plate, with no mechanical movement. Also works as an access control keypad. Two search buttons are used to scroll through the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. Integrated RFID reader which can be used in conjunction with Simplekey. Complete with SBC a/v unit part. 4680C for audio/video/door lock management, and flush-mounted box with concealed fixing screws. Dimensions 342x182x3 mm.



General specifications

Vandal Resistant IK: **Yes**

Compatibility

Video door entry family: **Yes**

Simplebus Top system: **Yes**

Simplebus Color system: **Yes**

Mounting/Installation

Flush-mounted: **Yes**

Audio/video specifications

Display size (inches): **3'**

Display resolution (H x V): **128x68 DOTS**

Audio system: **No**

Audio/video system: **Yes**

Type of display: **LCD**

Hardware specifications

DDE function: **Yes**

Sensitive Touch technology: **Yes**

Software/firmware specifications

No. of storable users: **4000**

Connectivity

Type of connections/ports: **RS485, USB, ETH**

DATA SHEET

Ethernet ports:	1
RS485 ports:	2

Functions - Settings

Key button function:	Yes
Loudspeaker volume control:	Yes

Technical properties

Temperature range (°C):	-25/55°C
-------------------------	----------

Electrical specifications

Maximum current absorption (mA):	250
----------------------------------	-----