DATA SHEET

COD. 3454

TOUCH SCREEN STAINLESS STEEL A/V ENTRANCE PANEL - VIP

Stainless steel flush-mounted entrance panel with 7" capacitive touch screen with impact-proof glass. Configurable graphics (list of names with search, up to 60 virtual buttons (or 10 with images, name directory, access codes up to 8 digits). Integrated RFID reader which can be used in conjunction with Simplekey. Users and settings are simple to program using VIP Manager part. 1449. It is compatible with all VIP products and functions. Pre-assembed with VIP a/v unit part. 4682C for audio/video/door lock management, and flush-mounted box with concealed fixing screws. Dimensions 342x182x3 mm.



General specifications

Vandal Resistant IK:

Compatibility

 Video door entry family:
 Yes

 Vip system:
 Yes

Mounting/Installation

Flush-mounted: Yes

Audio/video specifications

 Signal/noise ratio (dB):
 48

 Angle of view on 3 axes (°):
 D:80,27 H:67.07 V:47,37

 Display size (inches):
 8'

 Camera pixels (H x V):
 500x582

 Display resolution (H x V):
 800x480

 Audio system:
 No

 Audio/video system:
 Yes

 Type of display:
 CAPACITIVE TOUCH

Hardware specifications

DDE function: Yes

Connectivity

Type of connections/ports:	RS485, ETH
Ethernet ports:	1
RS485 ports:	2



DATA SHEET

i unicuona - acuniga	Fun	ctions	-	Settings
----------------------	-----	--------	---	----------

Key button function:	Yes
Loudspeaker volume control:	Yes

Technical properties

Temperature range (°C):	-25°C/+55°C	
remperature range (O).	20 0/100 0	

Electrical specifications

Absorption:	25W	

General info

Product height (mm):	342
Product width (mm):	182
Product depth (mm):	60

Packaging

Single pack height (mm):	125	
Single pack width (mm):	231	
Single pack weight (g):	4300	
Single pack depth (mm):	512	

